

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
4 December 2003 (04.12.2003)

PCT


(10) International Publication Number
WO 03/099360 A1

- (51) International Patent Classification⁷: **A61M 11/06**
- (21) International Application Number: **PCT/IT02/00680**
- (22) International Filing Date: 25 October 2002 (25.10.2002)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PR2002A000027 28 May 2002 (28.05.2002) IT
- (71) Applicant (for all designated States except US): **MEDEL S.P.A.** [IT/IT]; Via Micheli, 7, Fraz. San Polo, I-43056 Torricella (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TROMBI, Andrea** [IT/IT]; Via Brigate Matteotti, 4, I-43100 Parma (IT).
- (74) Agent: **GOTRA, Stefano**; Bugnion S.p.a, Via Garibaldi, 22, I-43100 Parma (IT).

- (81) Designated States (*national*): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK (utility model), SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **NEBULISER**



(57) Abstract: Nebuliser ampoule (2), in particular for aerosol therapy, of the type comprising an outlet (3) for dispensing a nebulised medical product, an element (4) for distributing the medical product and an element (5) for activating the nebulisation. The ampoule (2) is characterised in that the activator element (5) is physically separate from the element (4) for distributing the medical product. The distributor element (4) comprises a nozzle (6) for injecting a flow of air, called primary flow, inside the ampoule (2), said flow being necessary for generating the nebulisation, and at least a substantially conical body (7) inserted on the nozzle (6) and provided with at least a channel for conveying the medical product from a tank (8) of the ampoule (2) to a nebulisation area.

WO 03/099360 A1

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB,

GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designation US
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

NEBULISER

TECHNICAL FIELD AND BACKGROUND ART.

The present invention relates to a nebuliser ampoule, in particular for aerosol therapy, of the type comprising a mouthpiece for dispensing a nebulised medical product, an element for distributing the medical product and an element for activating the nebulisation.

As is well known, apparatuses for nebulising are used in particular in the field of aerosol therapy, i.e. of the therapeutic treatment of symptoms of the respiratory track, such as asthmatic or bronchial symptoms. Said therapeutic system provides for the generation of an aerosol, i.e. of a dispersion or nebulisation of appropriate medical liquids that act through the inhalation of the medical liquid itself.

Such apparatuses are widely used, especially in the case of paediatric therapies, and are provided in different formats able to meet different users' requirements. More specifically, nebulising apparatuses can also be constructed in portable formats, so that the user can have the necessary medicine available at any time, especially in the case of ailments entailing frequent or unpredictable respiratory crises, such as asthmatic ailments.

Pneumatic nebulising apparatuses also exist, so defined because they comprise a compressor that aspirates air from the environment and sends it to a nebulising ampoule containing the medical liquid.

Some pneumatic nebulisation apparatuses comprise, in addition to a primary conduit for the delivery of a flow of air necessary for nebulisation, and called primary flow, also a so-called supplementary, or secondary, channel,

provided with an inlet through which ambient air enters by Venturi effect and because of the aspiration provided by the user during inspiration.

The flow of air of the secondary channel, called secondary flow, allows a better nebulisation of the medical product, in terms of quantity and quality of the generated spray.

During the expiration phase, the air exhaled by the user is expelled from the apparatus by means of an outlet.

Normally, both the inlet of the secondary channel and the outlet are provided with a valve, able to move between an opened position and a closed position to guarantee that the flow of air inside the apparatus is correctly directed, both during inspiration and during expiration. In particular, said valves are usually made of highly deformable plastic material and are actuated directly by the flow of air that impacts thereon.

Generally, the tank of the nebuliser ampoule is open superiorly and is provided inferiorly with a nozzle for the entry of the air coming from the primary delivery conduit of the compressor. On the nozzle is inserted a cone which deviates the flow of the air and draws the liquid from the tank through some channels, usually obtained on the cone itself. The cone-channels assembly is usually called medical product distributor element.

The channels are usually a pair of grooves obtained on opposite parts of the lateral surface of the cone, to enable the liquid to pass between the body of the cone and the nozzle for the entrance of the air inside the ampoule.

To enable the intake of the liquid through the channels, and consequently the nebulisation, a so-called nebulisation activator element is necessary.

In accordance with a possible prior art technique, said element is made in a

single piece with the cone and is positioned in correspondence with an outlet of the nozzle.

The activator element is integral with a platelet with rectangular section, positioned parallel to the flow of air exiting the nozzle. Said platelet is connected to cone, generally by means of a pair of supports positioned on an edge of the cone itself in diametrical position. The flow of air coming from the primary conduit, impacting against the activator element, forms a pair of vortices that are able to generate such a turbulence as to create a vacuum in correspondence with the outlet of the nozzle.

In this way, the medical liquid is aspirated and rises along the channels present on the cone, mixing itself with the air of the delivery conduit (and possible with the air coming from the supplementary channel) and thereby forming the aerosol.

In regard to the compressor, it is generally housed in a rigid case, made for instance of plastic material, which incorporates the outlets of the intake and delivery conduits coming from the compressor itself. In use, mainly with traditional apparatuses, in particular for home use, the rigid case containing the compressor is usually set down on a plane whilst the nebulising ampoule is located in proximity to the user's face and is connected to the inlet of the delivery conduit by means of a flexible pipeline.

The compressor can comprise a header incorporating both the aspiration conduit and the delivery conduit, interfacing directly with the exterior by means of intakes obtained directly on the header itself and destined to be adapted to the profile of the rigid containment case.

Nebuliser ampoules provided with an activator element made of a single

piece with the distributor have some important drawbacks.

First of all, because of the presence of the supports of the platelet, it is impossible to assure a flow of air that is substantially symmetrical relative to the axis of the primary conduit. Consequently, the nebulisation that is formed inside the ampoule is not homogeneous.

In the second place, the presence of the supports forces to construct a single pair of channels for aspirating the medical product. Given the geometry of the distributor and of the activator element, the supports inevitably interfere with at least a pair of channels positioned in correspondence with a diameter of the cone, compromising a correct distribution of the medical liquid inside the flow of air present in the ampoule.

DISCLOSURE OF THE INVENTION.

The aim of the present invention is to eliminate the aforesaid drawbacks making available a nebuliser ampoule provided with an activator element able to assure a primary flow of air, substantially symmetrical relative to the axis of the primary conduit.

Another aim of the present invention is to propose a nebuliser ampoule provided with a distributor element which allows to obtain any number of channels, regardless of the presence of the activator element.

An additional aim of the present invention is to make available a nebuliser ampoule provided with an activator element which does not interfere with the fluid dynamics of the spray in correspondence with the so-called aerosol generation plane, this term defining the space of the ampoule just outside the cone and around it.

Yet another aim of the present invention is to obtain a nebuliser ampoule

provided with means for selecting the dimensions of the particles present in the spray, to improve the therapeutic effect of the medical product dispensed by the ampoule.

Said aims are fully achieved by the nebuliser ampoule, in particular for aerosol therapy, of the present invention, which is characterised by the content of the claims set out below and in particular in that the element for activating the nebulisation is physically separate from the element for distributing the medical product. The term "physically separate" means that the activator element is not made in a single piece with the distributor element and hence is distinct therefrom. However, it would be possible to interconnect the activator element and the distributor element, for instance by means of a snap-on coupling.

In particular, the distributor element comprises at least a nozzle for injecting a primary flow of air inside the ampoule to generate the nebulisation. The distributor element is provided with at least a preferably conical coating body, inserted on the nozzle and provided with at least a channel to convey the medical product from a tank of the ampoule to a nebulisation area.

BEST MODE FOR CARRYING OUT THE INVENTION.

These aims and other aims will become more readily apparent from the description that follows of a preferred embodiment illustrated, purely by way of non limiting example, in the accompanying drawing tables, in which:

- Figure 1 shows a partially section front view of an apparatus for aerosol therapy provided with a nebuliser ampoule according to the invention;
- Figure 2 shows a top view of the apparatus of Figure 1;
- Figure 3 shows a lateral view of the ampoule of the apparatus shown in

Figure 1;

- Figure 4 shows a plan view of the ampoule of Figure 3, enlarged and sectioned according to the trace I-I;
- Figure 5 shows a top view of the ampoule shown in Figure 3, with some parts remove the better to highlight others;
- Figure 6 shows an exploded view of the apparatus of Figure 1.

With reference to the figures, the apparatus for aerosol therapy is globally indicated with the number 1 and comprises a nebuliser ampoule 2 provided with a mouthpiece 3 for dispensing a nebulised medical product.

The nebuliser ampoule 2 originally comprises an element 4 for distributing the medical product, physically separate from an element 5 for activating the nebulisation. The term "physically separate" means that the activator element 5 is not made in a single piece with the distributor element 4 and hence is distinct therefrom, but is able in any case to be interconnected thereto, for instance by means of snap-on coupling.

In the illustrated embodiment, the distributor element 4 comprises a nozzle 6 for injecting a primary flow of air inside the ampoule 2, said flow being necessary for generating the nebulisation.

The distributor element 4 comprises a coating body 7, preferably conical, inserted on the nozzle 6 and provided with at least a channel (not shown herein) for conveying the medical product from a tank 8 of the ampoule 2 to a nebulisation area. In particular, one or two channels can be obtained by means of a plurality of grooves preferably provided on opposite parts of a lateral surface of the coating body 7.

With particular reference to Figure 6, the coating body 7 has portions 7a

defining extensions of the lateral walls 9a of the secondary channel 9. In the illustrated embodiment, said portions consist of a ring connected to the coating body 7 by means of supporting element 7b. In particular, the ring is positioned in correspondence with the lower ends of the lateral walls 9a of the secondary channel.

In regard to the activator element 5, it has a portion 5a having substantially circular section. In particular, the activator element 5 is superposed to the nozzle 6 at a pre-set distance from an outlet 6a thereof.

The nebuliser ampoule 2 comprises a supplementary, or secondary, channel 9, for introducing a secondary flow of air inside the ampoule 2, in order to increase the nebulisation of the medical product. In the illustrated embodiment, the secondary channel 9 is coaxial to the distributor element 4 and is provided with lateral walls 9a that extend below an outlet 6a of the distributor element 4 or in any case below a plane for generating the nebulisation (indicated with the arrow A in Figure 1). Specifically, the lateral walls 9a serve as means for selecting the particles that compose the nebulised medical product. In particular, the lateral walls 9a, together with the secondary flow of air, force the particles having larger dimensions to re-settle in the tank 8 of the ampoule 2. An aerosol formed by particles of small dimensions has better therapeutic effectiveness, because it penetrates in depth in the user's respiratory tract.

The activator element 5 is retained in position by means of a plurality of supports 5b connected to the secondary channel 9 and preferably made in a single body with the activator element itself. Specifically, said supports are arranged radially to the secondary channel and are preferably three. In the

illustrated embodiment, the activator element 5 and the related supports 5b are made in a single piece with the secondary channel 9.

In an alternative and not illustrated embodiment, it is possible for the activator element 5 and the related supports 5b, while possibly being part of a single body, to be made in a distinct piece from the secondary channel.

The operation of the invention is as follows.

During inspiration, the vacuum generated inside the ampoule 2 draws air from the environment, opening a valve 10 usually present on an inlet of the secondary channel 9.

Simultaneously, the primary flow of air coming from the nozzle 6 impacts on the activator element 5, generating a turbulence that is able to create such a vacuum as to aspirate the medical liquid from the tank 8 and cause it to rise along the channels obtained on the coating body 7.

The liquid is subsequently expelled from the channels and mixed with the primary flow, generating the aerosol in correspondence with the plane of generation of the nebulisation.

The presence of the walls 9a that extend below the outlet 6a of the nozzle 6, forces the spray to follow the path indicated with the arrow B in Figure 1 and forces the larger particles (and hence the particles with greater inertia) to re-settle in the tank 8. The larger, and hence heavier, particles cannot flow by the walls 9a following the flow of air and therefore are not conveyed to the mouthpiece 3.

The secondary flow of air (whose motion is the one indicated by the arrow C in Figure 1) also contributes to select the particles, thrusting the aerosol towards the bottom of the ampoule 2.

The air exhaled by the user is expelled by means of an additional valve 11, preferably positioned on the mouthpiece 3.

The invention achieves important advantages.

5 First of all, the presence of the activator element 5 physically separate from the distributor element 4 assures a primary flow of air that is substantially symmetrical relative to the axis of the primary conduit and hence assures a homogeneous dispersion of the medical liquid.

10 Secondly, the activator element 5, being separate from the distributor element 4, does not interfere with the fluid dynamics of the spray in correspondence with the plane of generation of the aerosol.

An additional advantage of the present invention is represented by the possibility of obtaining, on the distributor element, any number of channels. Since the activator element 5 is separate from the distributor element 4, there are no supports that may interfere with the egress of medical liquid from the
15 channels themselves and/or with the formation of the aerosol.

Another advantage is given by the presence of the walls 9a of the secondary conduit, which allow to select the dimensions of the particles present in the spray, improving the therapeutic effect of the medical product dispensed by the ampoule 2.

CLAIMS

1. Nebuliser ampoule (2), in particular for aerosol therapy, of the type comprises:

at least a mouthpiece (3) for dispensing a nebulised medical product;

at least an element (4) for distributing the medical product;

5 at least an element (5) for activating the nebulisation,
characterised in that the activator element (5) is physically separate from the
element (4) for distributing the medical product.

2. Nebuliser ampoule as claimed in claim 1, characterised in that the
distributor element (4) comprises:

10 at least a nozzle (6) for injecting a flow of air, called primary flow, inside the
ampoule (2), said flow being necessary for generating the nebulisation;

at least a coating body (7) inserted on the nozzle (6) and provided with at
least a channel for conveying the medical product from a tank (8) of the
ampoule (2) to a nebulisation area.

15 3. Nebuliser ampoule as claimed in claim 2, characterised in that the
activator element (5) has a portion (5a) having substantially circular section
and is superposed to the nozzle (6) at a pre-set distance from an outlet (6a)
thereof.

4. Nebuliser ampoule as claimed in claim 1, characterised in that it
20 comprises means for selecting particles of the nebulisation having
predetermined dimensions.

5. Nebuliser ampoule as claimed in claim 1, characterised in that it
comprises a supplementary, or secondary, channel (9), for introducing a flow
of air, called secondary flow, into the ampoule (2) to increase and refine the

nebulisation of the medical product.

6. Nebuliser ampoule as claimed in claim 5, characterised in that the secondary channel (9) is coaxial to the distributor element (4).

5 7. Nebuliser ampoule as claimed in claim 5, characterised in that the activator element (5) is made of a single piece with the secondary channel (9).

8. Nebuliser ampoule as claimed in claim 5, characterised in that the secondary channel (9) is provided with lateral walls (9a) which extend below an outlet (6a) of the distributor element (4) or in any case below a plane of generation of the nebulisation.

10 9. Nebuliser ampoule as claimed in claim 8, characterised in that the coating body (7) has portions (7a) defining extensions of the lateral walls (9a) of the secondary conduit (9).

10. Nebuliser ampoule as claimed in claim 8, characterised in that said lateral walls (9a) define means for selecting particles of the nebulisation
15 having predetermined dimensions.

11. Nebuliser apparatus, in particular for aerosol therapy, characterised in that it comprises a nebuliser ampoule (2) as claimed in the previous claims.





FIG. 3




FIG. 5




FIG. 4





FIG. 6

INTERNATIONAL SEARCH REPORT

PCT/IT 02/00680

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61M11/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61M B05B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 620 021 A (GLENN JOSEPH G ;A & H PRODUCTS INC (US)) 19 October 1994 (1994-10-19) column 7, line 47 -column 9, line 6; figure 1	1,2,4-8, 10,11
X	US 5 503 139 A (MCMAHON MICHAEL D ET AL) 2 April 1996 (1996-04-02) column 3, line 38 -column 4, line 67; figures 1,2	1-7,11
X	EP 0 170 715 A (BRUGGER INGE;BRUGGER STEPHAN) 12 February 1986 (1986-02-12) page 9, line 16 -page 11, line 29; figure 3	1,4-6,8, 10,11



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

13 March 2003

Date of mailing of the international search report

24/03/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Zeinstra, H

INTERNATIONAL SEARCH REPORT

PCT/IT 02/00680

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
EP 0620021	A	19-10-1994	US	5209225 A	11-05-1993
			EP	0620021 A1	19-10-1994
			CA	2083241 A1	20-05-1993
<hr/>					
US 5503139	A	02-04-1996	AU	674472 B2	19-12-1996
			AU	1257695 A	21-08-1995
			CA	2157573 A1	10-08-1995
			EP	0691863 A1	17-01-1996
			JP	8508670 T	17-09-1996
			NZ	277378 A	24-02-1997
			WO	9520988 A1	10-08-1995
<hr/>					
EP 0170715	A	12-02-1986	EP	0170715 A1	12-02-1986
			AT	33447 T	15-04-1988
			DE	3470380 D1	19-05-1988
<hr/>					